

TITAN Telephone Router

Telephone Router

The TITAN *Telephone Router* provides connectivity to your telephone/PBX system, integrating voice-prompted wireless messaging from any telephone. Send text messages to any recipient in the system, whether via pager, cordless handset or even e-mail, all from any PBX extension on property. Each *Telephone Router* supports up to three telephone lines for PBX-programmed automatic roll-over to eliminate busy signals in high traffic environments.



See reverse side for detailed technical specifications.

TITAN for Healthcare

TITAN provides a comprehensive industrial-grade, modular and scalable messaging system that is custom-configured for the unique needs of each property. Whether you operate a large and dynamic resort facility, a business hotel or a limited-service property, TITAN is scalable to provide an appropriate communication management solution for every need and budget.



TITAN modules are commercial-grade 19" rack-mount or tabletop stackable appliances, providing secure web-browser access from any location, minimizing IT support needs.

TITAN...from the communications experts at JTECH Communications.

COMMUNICATE. ACKNOWLEDGE. EXECUTE.



Telephone Router



Technical Specifications

Equipment type	Multiport interactive voice response (IVR) module
Power supply	110-240VAC 50/60Hz 25W max
External led indicators.....	Power, IP link, IP activity, RS232 TX, RS232 RX, off hook x 3
External connectors	Ethernet: RJ45f 10/100 Mbps
.....	Serial RS232D: RJ45
.....	Telephone: Non-powered FXO analog ports RJ12 x 3 (requires analog lines/extensions)
.....	Power: IEC mains socket
Common messages	100 max
Supported protocols	RS232: TAP (PET/IXO)
.....	IP: RPC XML
Dimensions	Standard 19 inch rack case
.....	17.3 x 8.1 x 1.7 inches / 439 x 205 x 44 mm (without rack ears)
Weight	5.9lb / 2.7kg nett
Ambient temperature operating range	0 – 50 °C (20-90% RH non condensing)
Storage temperature range	-10 – 60 °C (10-95% RH non condensing)

Specifications subject to change without notice

COMMUNICATE. ACKNOWLEDGE. EXECUTE.